

APPENDIX

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS:

Please enter the following amended claims:

1. (Amended) A navigation system comprising:

a subscriber unit configured to receive and transmit information, the subscriber unit including a global positioning system mechanism to determine subscriber position information, an output mechanism to convey information to a subscriber, and a speech processing mechanism to accommodate communications between the subscriber unit and the subscriber; and

a service provider configured to communicate with the subscriber unit, the communications between the service provider and the subscriber unit including the reception and transmission of navigation information including map information,

wherein the output mechanism prompts the subscriber to speak destination information, the speech processing mechanism receives the destination information and the subscriber unit transmits the subscriber position information and the destination information to the service provider, and the service provider responds by transmitting the navigation information to the subscriber unit, which conveys the navigation information to the subscriber via the output mechanism,

wherein the navigation information involves a plurality of points along a route from a current position to a destination, and wherein the subscriber unit is configured to determine a distance between a current position and a position related to one or more points along the route, and

wherein the subscriber unit requests new map information from the service provider when the distance exceeds a predetermined distance.

6. (Amended) A navigation system comprising:

a subscriber unit configured to receive and transmit information, the subscriber unit including a global positioning system mechanism to determine subscriber position information, an output mechanism to convey information to a subscriber, and a speech processing mechanism to accommodate communications between the subscriber unit and the subscriber; and

a service provider configured to communicate with the subscriber unit, the communications between the service provider and the subscriber unit including the reception and transmission of navigation information including map information,

wherein the output mechanism prompts the subscriber to speak destination information, the speech processing mechanism receives the destination information and the subscriber unit transmits the subscriber position information and the destination information to the service provider, and the service provider responds by transmitting the navigation information to the subscriber unit, which conveys the navigation information to the subscriber via the output mechanism,

wherein each of the subscriber unit and the service provider encrypt information before transmitting the information, and

[the navigation system according to claim 5,] wherein each user of the subscriber unit is assigned an encryption key, the speech processing mechanism is configured to identify a user on the basis of the voice of the user, and the subscriber unit is configured to use the encryption key assigned to the identified user during navigation by the identified user.

A

10. (Amended) The navigation system according to claim [8] 1, wherein the subscriber unit is configured to notify the subscriber that the route has been deviated from when the distance exceeds a predetermined distance.

11. (Amended) A navigation system comprising:
a subscriber unit configured to receive and transmit information, the subscriber unit including a global positioning system mechanism to determine subscriber position information, an output mechanism to convey information to a subscriber, and a speech processing mechanism to accommodate communications between the subscriber unit and the subscriber; and

a service provider configured to communicate with the subscriber unit, the communications between the service provider and the subscriber unit including the reception and transmission of navigation information including map information,

wherein the output mechanism prompts the subscriber to speak destination information, the speech processing mechanism receives the destination information and the subscriber unit transmits the subscriber position information and the destination information to the service provider, and the service provider responds by transmitting the navigation information to the subscriber unit, which conveys the navigation information to the subscriber via the output mechanism, and

[The navigation system according to claim 1,] wherein the service provider is configured to store the subscriber position information, the subscriber unit is configured to measure the distance between the stored subscriber position information and a current position, and the subscriber unit transmits the current position to the service provider when the distance exceeds a predetermined distance.

15. (Amended) A navigation system comprising:

a subscriber unit configured to receive and transmit information, the subscriber unit including a global positioning system mechanism to determine subscriber position information, an output mechanism to convey information to a subscriber, and a speech processing mechanism to accommodate communications between the subscriber unit and the subscriber; and

a service provider configured to communicate with the subscriber unit, the communications between the service provider and the subscriber unit including the reception and transmission of navigation information including map information,

wherein the output mechanism prompts the subscriber to speak destination information, the speech processing mechanism receives the destination information and the subscriber unit transmits the subscriber position information and the destination information to the service provider, and the service provider responds by transmitting the navigation information to the subscriber unit, which conveys the navigation information to the subscriber via the output mechanism, and

[The navigation system according to claim 1,] wherein the subscriber unit includes a firmware and a software portion, the subscriber unit being configured to receive encrypted firmware and software upgrades, the upgrades being decrypted by, and programmed into, the subscriber unit.

17. (Amended) A navigation method comprising:

receiving, by a subscriber unit, position information and destination information, the destination information being spoken by a subscriber;



transmitting, by the subscriber unit, the position information and the destination information to a service provider;

receiving, by the subscriber unit, navigation information from the service provider, the navigation information involving a plurality of points along a route from a current position to a destination; [and]

conveying, by the subscriber unit, the navigation information to the subscriber;

encrypting, by each of the subscriber unit and the service provider, information before transmission;

assigning, by the subscriber unit, a first user of a subscriber unit an encryption key;

associating the encryption key of the first user with the voice of the first user;

identifying the first user when the first user speaks; and

using the encryption key assigned to the first user during navigation by the first user.

21. (Amended) A navigation method comprising:

receiving, by a subscriber unit, position information and destination information, the destination information being spoken by a subscriber;

transmitting, by the subscriber unit, the position information and the destination information to a service provider;

receiving, by the subscriber unit, navigation information from the service provider, the navigation information involving a plurality of points along a route from a current position to a destination;

conveying, by the subscriber unit, the navigation information to the subscriber;

encrypting, by each of the subscriber unit and the service provider, information before transmission; and

[The navigation method according to claim 18, further comprising]
receiving, by the subscriber unit, encrypted firmware or software upgrades.

22. (Amended) A navigation method comprising:
receiving, by a subscriber unit, position information and destination information, the
destination information being spoken by a subscriber;
transmitting, by the subscriber unit, the position information and the destination
information to a service provider;
receiving, by the subscriber unit, navigation information from the service provider, the
navigation information involving a plurality of points along a route from a current position to
a destination;
conveying, by the subscriber unit, the navigation information to the subscriber;

[The navigation method according to claim 16, further comprising:]
determining, by the subscriber unit, the distance between the current position and a
position related to one or more points along the route; and
requesting new map information from the service provider when the distance exceeds
a predetermined distance.

23. (Amended) A navigation method comprising:
receiving, by a subscriber unit, position information and destination information, the
destination information being spoken by a subscriber;
transmitting, by the subscriber unit, the position information and the destination
information to a service provider;

A

receiving, by the subscriber unit, navigation information from the service provider, the navigation information involving a plurality of points along a route from a current position to a destination;

conveying, by the subscriber unit, the navigation information to the subscriber;

[The navigation method according to claim 16, further comprising:]

storing, by the service provider, the position information;

measuring, by the subscriber unit, the distance between the stored position information and the current position; and

transmitting, by the subscriber unit, the current position to the service provider when the distance exceeds a predetermined distance.

24. (Amended) A computer-readable medium encoded with a plurality of processor-executable instruction sequences for:

receiving, by a subscriber unit, position information and destination information, the destination information being spoken by a subscriber;

transmitting, by the subscriber unit, the position information and the destination information to a service provider;

receiving, by the subscriber unit, navigation information from the service provider, the navigation information involving a plurality of points along a route from a current position to a destination; [and]

conveying, by the subscriber unit, the navigation information to the subscriber;

determining, by the subscriber unit, the distance between the current position and a position related to one or more points along the route; and

requesting new map information from the service provider when the distance exceeds a predetermined distance.

27. (Amended) A computer-readable medium encoded with a plurality of processor-executable instruction sequences for:

receiving, by a subscriber unit, position information and destination information, the destination information being spoken by a subscriber;

transmitting, by the subscriber unit, the position information and the destination information to a service provider;

receiving, by the subscriber unit, navigation information from the service provider, the navigation information involving a plurality of points along a route from a current position to a destination;

conveying, by the subscriber unit, the navigation information to the subscriber;

encrypting, by each of the subscriber unit and the service provider, information before transmission;

[The computer-readable medium of claim 26, further comprising processor-executable instruction sequences for:]

assigning, by the subscriber unit, a first user of a subscriber unit an encryption key;

associating the encryption key of the first user with the voice of the first user;

identifying the first user when the first user speaks; and

using the encryption key assigned to the first user during navigation by the first user.

30. (Amended) A computable-readable medium encoded with a plurality of processor-executable instruction sequences for:

receiving, by a subscriber unit, position information and destination information, the destination information being spoken by a subscriber;

transmitting, by the subscriber unit, the position information and the destination information to a service provider;

receiving, by the subscriber unit, navigation information from the service provider, the navigation information involving a plurality of points along a route from a current position to a destination;

conveying, by the subscriber unit, the navigation information to the subscriber;

[The computer-readable medium of claim 24, further comprising processor-executable instruction sequences for:]

storing, by the service provider, the position information;

measuring, by the subscriber unit, the distance between the stored position information and the current position; and

transmitting, by the subscriber unit, the current position to the service provider when the distance exceeds a predetermined distance.

A.